

# Introduction to 8086 Assembly

## Lecture 3

Object files, compiling, assembling and linking

# Compiling a C file



K. N. Toosi  
University of Technology

```
#include <stdio.h>
```

test.c

```
int main() {
```

```
    printf("Salaaaaam!!!\n");
```


```
    return 0;
```

```
}
```

# Compiling a C file




K. N. Toosi  
University of Technology



# Compiling a C file



K. N. Toosi  
University of Technology



```
b.nasihatkon@kntu:lecture3$ gcc test.c  
b.nasihatkon@kntu:lecture3$ ./a.out  
Salaaaaam!!!
```

# Compiling a C file



K. N. Toosi  
University of Technology

```
#include <stdio.h>
```

test.c

```
int main() {
```

```
    printf("Salaaaaam!!!\n");
```

```
    return 0;
```

```
}
```

```
b.nasihatkon@kntu:lecture3$ gcc test.c
b.nasihatkon@kntu:lecture3$ ./a.out
Salaaaaam!!!
```

# Compiling a C file



K. N. Toosi  
University of Technology

```
#include <stdio.h>
```

test.c

```
int main() {
```

```
    printf("Salaaaaam!!!\n");
```

```
    return 0;
```

```
}
```

Who wrote **printf**?

Where is the code for **printf**?

```
b.nasihatkon@kntu:lecture3$ gcc test.c
b.nasihatkon@kntu:lecture3$ ./a.out
Salaaaaam!!!
```

# Compiling a C file



K. N. Toosi  
University of Technology

test.c

```
extern int printf (const char *__restrict __format, ...);

int main() {

    printf("Salaaaaam!!!\n");

    return 0;
}
```

# Compiling a C file



K. N. Toosi  
University of Technology

test.c

```
extern int printf (const char *__restrict __format, ...);  
  
int main() {  
  
    printf("Salaaaaam!!!\n");  
  
    return 0;  
}
```

```
b.nasihatkon@kntu:lecture3$ gcc test.c  
b.nasihatkon@kntu:lecture3$ ./a.out  
Salaaaaam!!!  
b.nasihatkon@kntu:lecture3$
```

# Compiling a C file, object files




K. N. Toosi  
University of Technology



# Object files, libraries and linking




K. N. Toosi  
University of Technology



# Libraries



K. N. Toosi  
University of Technology



# Libraries




**K. N. Toosi**  
University of Technology

- Collection of object files
- Static vs. Dynamic Linking
- Shared Objects (SO), Dynamic-Link Libraries (DLL)

# Modular programming in C




K. N. Toosi  
University of Technology



# high-level to low-level hierarchy



K. N. Toosi  
University of Technology





# Object files

- Machine code + metadata (unresolved symbols, etc.)
  - for linking, debugging, etc.
  - [https://en.wikipedia.org/wiki/Object\\_file](https://en.wikipedia.org/wiki/Object_file)
  - [https://en.wikipedia.org/wiki/Object\\_code](https://en.wikipedia.org/wiki/Object_code)
- Object file formats
  - Common Object File Format (COFF)
  - Relocatable Object Module Format (OMF)
  - Executable and Linkable Format (ELF)

# Assembling assembly files



K. N. Toosi  
University of Technology



# Our first assembly program (64 bit)



K. N. Toosi  
University of Technology

```
segment .data
msg: db "Salaaaaaaam!!", 10 ; message + newline character

global _start

segment .text
_start: ; entry point (linker needs this)

    mov rax, 1 ; system call number (sys_write=1)
    mov rdi, 1 ; file descriptor (stdout=1)
    mov rsi, msg ; message to write
    mov rdx, 14 ; number of bytes to write

    syscall ; invoke system call (sys_write)

    mov rax, 60 ; system call number (sys_exit=60)
    mov rdi, 0 ; exit code 0

    syscall ; invoke system call (sys_exit)
```

look at: <http://cs.lmu.edu/~ray/notes/nasmtutorial/>

# Our first assembly program (64 bit)



K. N. Toosi  
University of Technology

```
segment .data
msg: db "Salaaaaaaam!!", 10 ; message + newline character

global _start

segment .text
_start: ; entry point (linker needs this)

    mov rax, 1 ; system call number (sys_write=1)
    mov rdi, 1 ; file descriptor (stdout=1)
    mov rsi, msg ; message to write
    mov rdx, 14 ; number of bytes to write

    syscall ; invoke system call (sys_write)

    mov rax, 60 ; system call number (sys_exit=60)
    mov rdi, 0 ; exit status (0)
    syscall ; invoke system call (sys_exit)
```

```
b.nasihatkon@kntu:lecture3$ nasm -f elf64 first.asm
b.nasihatkon@kntu:lecture3$ ld first.o
b.nasihatkon@kntu:lecture3$ ./a.out
Salaaaaaaam!!
```


look at: <http://cs.lmu.edu/~ray/notes/nasmtutorial/>

# Assembling, linking and running (64 bit)



K. N. Toosi  
University of Technology

- **Assemble:** `nasm -f elf64 first.asm`
- **Link:** `ld first.o`
- **Execute:** `./a.out`




# Assembling, linking and running (64 bit)



K. N. Toosi  
University of Technology

assembler                      create 64 bit ELF object file format                      input assembly file

```
nasm -f elf64 first.asm
```



# Our first assembly program (32 bit)



```
segment .data
msg:  db          "Salaaaaaaam!!", 10  ; message + newline character

segment .text
    global _start      ; make entry point visible

_start:                ; entry point (linker needs this)
    mov  edx, 14        ; message length
    mov  ecx, msg       ; address of message to write
    mov  ebx, 1         ; file descriptor (stdout=1)
    mov  eax, 4         ; (32 bit) system call number (sys_write=4)
    int  0x80          ; interrupt no. x80 = system call

    mov  eax, 1         ; (32 bit) system call number (sys_exit=1)
    int  0x80          ; interrupt no. x80 = system call
```

# Our first assembly program (32 bit)



```
segment .data
msg: db "Salaaaaaaam!!", 10 ; message + newline character

segment .text
    global _start ; make entry point visible

_start: ; entry point (linker needs this)
    mov     edx, 14 ; message length
    mov     ecx, msg ; address of message to write
    mov     ebx, 1 ; file descriptor (stdout=1)
    mov     eax, 4 ; (32 bit) system call number (sys_write=4)
    int     0x80 ; interrupt no. x80 = system call


    mov     eax, 1 ; (32 bit) system call number (sys_exit=1)
    int     0x80 ; interrupt no. x80 = system call
```

# Assembling, linking and running (32 bit)



K. N. Toosi  
University of Technology

- **Assemble:** `nasm -f elf first32.asm`
- **Link:** `ld -m elf_i386 first32.o`
- **Execute:** `./a.out`




# Assembling, linking and running (32 bit)



K. N. Toosi  
University of Technology

assembler                      create 32 bit ELF object file format                      input assembly file

```
nasm -f elf first32.asm
```




# Assembling, linking and running (32 bit)



K. N. Toosi  
University of Technology

linker                      create 32 bit executable                      input object file (32 bit ELF format)

```
ld -m elf_i386 first32.o
```



# Compiling and linking C files



K. N. Toosi  
University of Technology

test.c

```
#include <stdio.h>

int fact(int);

int main() {
    int x = 8;
    printf("x!=%d\n", fact(x));

    return 0;
}
```

fact.c

```
int fact(int n) {
    return n==0 ? 1 : n*fact(n-1);
}
```

# Compiling and linking C files



K. N. Toosi  
University of Technology



# Compiling and linking C files



# Compiling C files to 32 bit apps



K. N. Toosi  
University of Technology


Compile to 32 bit executable on a 64 bit system:

- First, install the 32 bit libraries:
  - `sudo apt-get install libc6-dev-i386`
  - `sudo apt-get install libx32gcc-4.8-dev`
  - `sudo apt-get install gcc-multilib`
- You might need to install:
  - `sudo apt-get install gcc-6-multilib`


# 32 bit Compiling and linking C files



K. N. Toosi  
University of Technology



# 32 bit Compiling and linking C files



# Our second assembly program!



K. N. Toosi  
University of Technology

- We do (mostly) 32 bit assembly
- We use the functions/macros from the book (Carter, *PC Assembly Language*, 2007) for IO

# I/O functions and macros from the book




K. N. Toosi  
University of Technology

|                                    |   |
|------------------------------------|---|
| <code>call print_int</code>        | prints EAX as signed integer  |
| <code>call print_char</code>       | prints the character whose ascii code is stored in AL   |
| <code>call print_string</code>     | prints the string whose starting address is stored in EAX, string must be null-terminated (C-string)    |
| <code>call print_nl</code>         | prints a newline character  |
| <code>call read_int</code>         | reads an integer from standard input and stores it into EAX   |
| <code>call read_char</code>        | read a character from standard input and stores its ascii code in EAX                                   |
| <code>dump_regs &lt;num&gt;</code> | (MACRO) prints out values of registers and flags (<num> is some number like 12 making debugging easier) |

# Our second assembly program!



K. N. Toosi  
University of Technology





# steps to run our program

0. Install the Netwide Assembler
  - `sudo apt install nasm`
1. Download the example files (including IO files) from the books website:  
<http://pacman128.github.io/pcasm/>
  - for linux click on the link [linux examples](#) to download the files
  - there are links for other platforms as well
2. Copy the files `asm_io.inc`, `asm_io.asm` and `cdecl.h` to your current working directory.
3. Compile the file `asm_io.asm` to object file (creating `asm_io.o`)
  - `nasm -f elf -d ELF_TYPE asm_io.asm`
4. Create a file named `driver.c`

# steps to run our program



K. N. Toosi  
University of Technology

4. Create a file named `driver.c` simply calling an assembly function:

```
void asm_main();

int main() {

    asm_main();

    return 0;

}
```

(alternatively, copy the files `driver.c` and `cdecl.h` to your current directory.)

# steps to run our program



## 5. Install the 32 bit C libraries (if not installed)

- `sudo apt-get install libc6-dev-i386`
- `sudo apt-get install libx32gcc-4.8-dev`
- `sudo apt-get install gcc-multilib (if needed)`
- `sudo apt-get install gcc-6-multilib (if needed)`

## 6. Compile driver.c to 32 bit object file (creating driver.o)

- `gcc -m32 -c driver.c`

# steps to run our program



7. Create your main assembly file containing the `asm_main` label
  - here the file named `myprog.asm` and looks like this:

```
%include "asm_io.inc"

segment .text

global asm_main

asm_main:
    enter 0,0
    pusha

    mov eax, 100
    mov ebx, 20
    sub eax, ebx

    call print_int    ; print EAX
    call print_nl    ; print a new line

    dump_regs 1111    ; printing the system state (registers, etc.)

    popa
    leave
    ret
```

# steps to run our program



7. Create your main assembly file containing the `asm_main` label
  - here the file named `myprog.asm` and looks like this:

```
%include "asm_io.inc"

segment .text

global asm_main

asm_main:
    enter 0,0
    pusha

    mov eax, 100
    mov ebx, 20
    sub eax, ebx

    call print_int      ; print EAX
    call print_nl      ; print a new line

    dump_regs 1111    ; print registers, etc

    popa
    leave
    ret
```

`myprog.asm`

```
void asm_main();

int main() {

    asm_main();

    return 0;

}
```

`driver.c`




# steps to run our program

8. Compile your assembly code to 32 bit object file (creating `myprog.o`)
  - `nasm -f elf myprog.asm`
9. link the object files `myprog.o`, `asm_io.o`, `driver.o` (and the C libraries) to create the executable
  - `gcc -m32 driver.o myprog.o asm_io.o`
10. run the executable and see the output
  - `./a.out`

# steps to run our program



K. N. Toosi  
University of Technology



# steps to run our program



K. N. Toosi  
University of Technology

myprog.asm

```
%include "asm_io.inc"

segment .text

global asm_main

asm_main:
    enter 0,0
    pusha

    mov eax, 100
    mov ebx, 20
    sub eax, ebx

    call print_int ; print E
    call print_nl  ; print e
    dump_regs 1111 ; print 1

    popa
    leave
    ret
```

driver.c

```
void asm_main();

int main() {

    asm_main();

    return 0;
}
```

```
nasihatkon@kntu:lecture3$ nasm -f elf -d ELF_TYPE asm_io.asm
nasihatkon@kntu:lecture3$ gcc -m32 -c driver.c
nasihatkon@kntu:lecture3$ nasm -f elf myprog.asm
nasihatkon@kntu:lecture3$ gcc -m32 driver.o myprog.o asm_io.o
nasihatkon@kntu:lecture3$ ./a.out
```

80  
Register Dump # 1111

```
EAX = 00000050 EBX = 00000014 ECX = FFDBFCB0 EDX = FFDBFCD4
ESI = F76B7000 EDI = F76B7000 EBP = FFDBFC88 ESP = FFDBFC68
EIP = 080484EB FLAGS = 0206 PF
```

# All commands



K. N. Toosi  
University of Technology

```
nasm -f elf -d ELF_TYPE asm_io.asm
```

```
gcc -m32 -c driver.c
```

```
nasm -f elf myprog.asm
```

```
gcc -m32 driver.o myprog.o asm_io.o
```

```
./a.out
```

# Give output file a name (-o option)



K. N. Toosi  
University of Technology

```
nasm -f elf -d ELF_TYPE asm_io.asm
```

```
gcc -m32 -c driver.c
```

```
nasm -f elf myprog.asm
```

```
gcc -m32 driver.o myprog.o asm_io.o -o myprog
```

```
./myprog
```

# Writing your own program



K. N. Toosi  
University of Technology

- Take the same steps as above
- Your source file should be like this (or use `ske1.asm` from the book file)

```
%include "asm_io.inc"

segment .text

global asm_main

asm_main:
    enter 0,0
    pusha

    ; write your assembly code here!

    popa
    leave
    ret
```