

Introduction to 8086 Assembly

Lecture 11

**Modular Programming
in C and Assembly**

Modular Programming



K. N. Toosi
University of Technology

test.c

```
#include <stdio.h>

extern int fact(int);

extern int maxval;

int main() {
    int x = 8;
    printf("x!=%d\n", fact(x));

    return 0;
}
```

fact.c

```
int maxval = 2;
static int flag = 1;

int fact(int n) {
    return n==0 ? 1 : n*fact(n-1);
}

static int condmax(int a, int b) {
    return (a > b && flag) ? a : b;
}
```

Modular Programming



K. N. Toosi
University of Technology

test.c

```
#include <stdio.h>

int fact(int);

extern int maxval;

int main() {
    int x = 8;
    printf("x!=%d\n", fact(x));

    return 0;
}
```

fact.c

```
int maxval = 2;
static int flag = 1;


int fact(int n) {
    return n==0 ? 1 : n*fact(n-1);
}

static int condmax(int a, int b) {
    return (a > b && flag) ? a : b;
}
```

Remember: Compiling and linking C files




K. N. Toosi
University of Technology



Remember: Compiling and linking C files




K. N. Toosi
University of Technology



Remember: Compiling and linking C files




K. N. Toosi
University of Technology




32 bit Compiling and linking C files



K. N. Toosi
University of Technology




32 bit Compiling and linking C files



Makefile



K. N. Toosi
University of Technology



target



Makefile

```
a.out: test.o fact.o
    gcc -m32 test.o fact.o

test.o: test.c
    gcc -m32 -c test.c


fact.o: fact.c
    gcc -m32 -c fact.c
```

Makefile



K. N. Toosi
University of Technology

```
gcc -m32 -c test.c
```



```
gcc -m32 -c fact.c
```

```
gcc -m32 test.o fact.o
```

```
a.out: test.o fact.o  
    gcc -m32 test.o fact.o
```

```
test.o: test.c  
    gcc -m32 -c test.c
```

```
fact.o: fact.c  
    gcc -m32 -c fact.c
```

Makefile


```
b.nasihatkon@kntu:modular_c$ make  
gcc -m32 -c test.c  
gcc -m32 -c fact.c  
gcc -m32 test.o fact.o
```

Makefile



K. N. Toosi
University of Technology

```
gcc -m32 -c test.c
```



change `test.c` and run
make again:

```
a.out: test.o fact.o
```

```
gcc -m32 test.o fact.o
```

```
test.o: test.c
```

```
gcc -m32 -c test.c
```

```
fact.o: fact.c
```

```
gcc -m32 -c fact.c
```


Makefile

Makefile



K. N. Toosi
University of Technology

```
gcc -m32 -c test.c
```



```
gcc -m32 -c fact.c
```

```
gcc -m32 test.o fact.o
```

```
a.out: test.o fact.o  
    gcc -m32 test.o fact.o
```

```
test.o: test.c  
    gcc -m32 -c test.c
```

```
fact.o: fact.c  
    gcc -m32 -c fact.c
```

Makefile

change `test.c` and run
make again:


```
b.nasihatkon@kntu:modular_c$ make  
gcc -m32 -c test.c  
gcc -m32 test.o fact.o
```

Makefile



K. N. Toosi
University of Technology

```
gcc -m32 -c test.c
```



change nothing and
rerun make:

```
a.out: test.o fact.o  
    gcc -m32 test.o fact.o
```

```
test.o: test.c  
    gcc -m32 -c test.c
```

```
fact.o: fact.c  
    gcc -m32 -c fact.c
```

Makefile

Makefile



K. N. Toosi
University of Technology

```
gcc -m32 -c test.c
```



```
gcc -m32 -c fact.c
```



```
gcc -m32 test.o fact.o
```



change nothing and rerun make:

```
Makefile
a.out: test.o fact.o
    gcc -m32 test.o fact.o

test.o: test.c
    gcc -m32 -c test.c

fact.o: fact.c
    gcc -m32 -c fact.c
```

```
b.nasihatkon@kntu:modular_c$ make
make: 'a.out' is up to date.
```

Makefile



K. N. Toosi
University of Technology

- More on Makefile
 - <http://www.cs.colby.edu/maxwell/courses/tutorials/maketutor/>
 - <https://www.tutorialspoint.com/makefile/>

Modular Programming in assembly




K. N. Toosi
University of Technology

- Multiple object files
- We have already done it!

We have already done it!




K. N. Toosi
University of Technology



We have already done it!



K. N. Toosi
University of Technology



Modular Programming in Assembly



K. N. Toosi
University of Technology

first.asm

```
extern fact, var1

segment .text

    mov eax, [var1]

    push 6
    call fact
    add esp, 4
```

second.asm

```
global fact, var1

segment .data

var1:    dd    22

segment .text

fact:
    ;; factorial function
```

Practice:

```
%include "asm_io.inc"
```

```
segment .text
```

```
global asm_main
```

```
extern fact, var1
```

```
asm_main:
```

```
pusha
```

```
mov eax, [var1]
```

```
call print_int
```

```
call print_nl
```

```
;; compute fact(6)
```

```
push 6
```

```
call fact
```

```
add esp, 4
```

```
call print_int
```

```
call print_nl
```

```
popa
```

```
ret
```

first.asm

```
global fact, var1
```

```
segment .data
```

```
var1: dd 22
```

```
segment .text
```

```
fact:
```

```
enter 0,0
```

```
mov eax, [ebp+8]
```

```
cmp eax, 0
```

```
jg recur
```

```
mov eax, 1
```

```
jmp endfact
```

```
recur:
```

```
dec eax
```

```
push eax
```

```
call fact
```

```
add esp, 4
```

```
imul dword [ebp+8]
```

```
endfact:
```

```
leave
```

```
ret
```

second.asm



K. N. Toosi
University of Technology

Practice:

```
%include "asm_io.inc"
```

first.asm

```
segment .text
```

```
global asm_main
```

```
extern fact, var1
```

```
asm_main:
```

```
pusha
```

```
mov eax, [var1]
```

```
call print_int
```

```
call print_nl
```

```
;; compute fact(6)
```

```
push 6
```

```
call fact
```

```
add esp, 4
```

```
call print_int
```

```
call print_nl
```

```
popa
```

```
ret
```

```
global fact, var1
```

```
segment .data
```

```
var1: dd 22
```

```
segment .text
```

```
fact:
```

```
enter 0,0
```

```
mov eax, [ebp+8]
```

```
cmp eax, 0
```

```
jg recur
```

```
mov eax, 1
```

```
jmp endfact
```

```
recur:
```

```
dec eax
```

```
push eax
```

```
call fact
```

```
add esp, 4
```

```
imul dword [ebp+8]
```

```
endfact:
```

```
leave
```

```
ret
```

second.asm



Practice:

```
%include "asm_io.inc"
```

first.asm

```
segment .text
```

```
global asm_main
```

```
extern fact, var1
```

```
asm_main:
```

```
pusha
```

```
mov eax, [var1]
```

```
call print_int
```

```
call print_nl
```

```
;; compute fact(6)
```

```
push 6
```

```
call fact
```

```
add esp, 4
```

```
call print_int
```

```
call print_nl
```

```
popa
```

```
ret
```

```
global fact, var1
```

```
segment .data
```

```
var1: dd 22
```

```
segment .text
```

```
fact:
```

```
enter 0,0
```

```
mov eax, [ebp+8]
```

```
cmp eax, 0
```

```
jg recur
```

```
mov eax, 1
```

```
jmp endfact
```

```
recur:
```

```
dec eax
```

```
push eax
```

```
call fact
```

```
add esp, 4
```

```
imul dword [ebp+8]
```

```
endfact:
```

```
leave
```

```
ret
```

second.asm



Practice:



K. N. Toosi
University of Technology

```
%include "asm_io.inc"  
segment .text
```

first.asm

```
global fact, var1  
segment .data  
var1: dd 22
```

second.asm

```
segment .text  
fact:
```

How to assemble & link?

```
$ nasm -f elf first.asm
```

```
$ nasm -f elf second.asm
```

```
$ gcc -m32 -o first driver.c first.o second.o asm_io.o
```

How to run?

```
$ ./first
```

```
call print_nl
```

```
popa  
ret
```

```
endfact:
```

```
leave  
ret
```

Using Makefile



K. N. Toosi
University of Technology

Makefile

```
GCC_OPTIONS= -m32
```

```
first: driver.o first.o second.o asm_io.o  
    gcc $(GCC_OPTIONS) -o first driver.o first.o second.o asm_io.o
```

```
first.o: first.asm asm_io.inc  
    nasm -f elf first.asm
```

```
second.o: second.asm asm_io.inc  
    nasm -f elf second.asm
```

```
asm_io.o: asm_io.asm  
    nasm -f elf -d ELF_TYPE asm_io.asm
```

```
driver.o: driver.c  
    gcc $(GCC_OPTIONS) -c driver.c
```

```
$ nasm -f elf first.asm  
$ nasm -f elf second.asm  
$ gcc -m32 -o first driver.c first.o second.o asm_io.o
```


Using Makefile



Makefile

```
GCC_OPTIONS= -m32
```

```
first: driver.o first.o second.o asm_io.o
```

```
gcc $(GCC_OPTIONS) -o first driver.o first.o second.o asm_io.o
```

```
first.o: first.asm asm_io.in  
nasm -f elf first.asm
```

```
second.o: second.asm asm_io.in  
nasm -f elf second.asm
```

```
asm_io.o: asm_io.asm  
nasm -f elf -d ELF_TYPE asm_io.asm
```

```
driver.o: driver.c  
gcc $(GCC_OPTIONS) -c driver.c
```

```
b.nasihatkon@kntu:lecture11$ ls  
1.html          driver.c        Makefile        second.asm  
asm_io.asm      first           modular_c      second.asm.html  
asm_io.asm.html first.asm       README         template.asm  
asm_io.inc      first.asm.html run.sh         template.c  
b.nasihatkon@kntu:lecture11$ make  
gcc -m32 -c driver.c  
nasm -f elf first.asm  
nasm -f elf second.asm  
nasm -f elf -d ELF_TYPE asm_io.asm  
gcc -m32 -o first driver.o first.o second.o asm_io.o  
b.nasihatkon@kntu:lecture11$ ./first  
22  
720  
b.nasihatkon@kntu:lecture11$ make  
make: 'first' is up to date.  
b.nasihatkon@kntu:lecture11$
```

Practice:



K. N. Toosi
University of Technology

```
%include "asm_io.inc"
```

first.asm

```
segment .text
```

```
global asm_main
```

```
extern fact, var1
```

```
asm_main:
```

```
pusha
```

```
mov eax, [var1]
```

```
call print_int
```

```
call print_nl
```

```
;; compute fact(6)
```

```
push 6
```

```
call fact
```

```
add esp, 4
```

```
call print_int
```

```
call print_nl
```

```
popa
```

```
ret
```

```
global fact, var1
```

```
segment .data
```

```
var1: dd 22
```

second.asm

```
segment .text
```

```
fact:
```

Why have not `print_int` and `print_nl` been defined as `extern`?

```
endfact:
```

```
leave
```

```
ret
```

Practice:



K. N. Toosi
University of Technology

```
%include "asm_io.inc"  
segment .text  
global asm_main  
extern fact, var1
```



```
asm_main:  
    pusha  
  
    mov eax, [var1]  
    call print_int  
    call print_nl  
  
    ;; compute fact(6)  
    push 6  
    call fact  
    add esp, 4  
  
    call print_int  
    call print_nl  
  
    popa  
    ret
```

first.asm

```
global fact, var1  
segment .data  
var1: dd 22
```

```
segment .text  
fact:
```

second.asm

Why have not `print_int` and `print_nl` been defined as `extern`?

- Look at `asm_io.inc`

```
endfact:  
    leave  
    ret
```

Practice:



```
%include "asm_io.inc"
```

first.asm

```
segment .text
```

```
global asm_main
```

```
extern fact, var1
```

```
asm_main:
```

```
pusha
```

```
mov eax, [var1]
```

```
call print_int
```

```
call print_nl
```

```
;; compute fact(6)
```

```
push 6
```

```
call fact
```

```
add esp, 4
```

```
call print_int
```

```
call print_nl
```

```
popa
```

```
ret
```

asm_io.inc

```
extern read_int, print_int, print_uint, print_string
```

```
extern read_char, print_char, print_nl
```

```
extern sub_dump_regs, sub_dump_mem, sub_dump_math, sub_dump_stack
```

```
%macro dump_regs 1
```

```
push dword %1
```

```
call sub_dump_regs
```

```
%endmacro
```

```
; usage: dump_mem label, start-address, # paragraphs
```

```
%macro dump_mem 3
```

```
push dword %1
```

```
push dword %2
```

```
push dword %3
```

```
call sub_dump_mem
```

```
%endmacro
```

```
:
```

```
:
```